

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6765)

Set ¼ sec. post, from which
An Oak 10" dia., bears N.70°W., 20 lks.
An Oak 12" dia., bears S.82°E., 31 lks.

Ben B. Irving, Deputy County Surveyor - Wit: N.E. Richardson;
Loren Weber - Aug. 1, 1940 - C.S. File 16/55

Location identified from one original BT scribed ¼ S.
Drove 1" x 36" Iron pipe 36" in ground with 2"x4" Oak stake
alongside for corner, from which
A Cedar 26" dia., bears S.25°W., 13.5 ft. mkd. ¼ S27 CS BT
A Fir 6" dia., bears North, 5.7 ft. mkd. ¼ S22 CS BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage &
W. Penley, crew - Dec. 1968 - C.S. File 54/73-53

Found - 2 x 4 scribed post "¼S CS". No trace of I.P.
26" now 32" Cedar S.25°W., 13.5 ft., shows good scar
6" now 14" D.Fir North, 5.7 ft., tree opened, scribe
marks visible.

(Logged to the West, probably when I.P. was pulled.)
Set Brass cap at cor. mkd: County Surveyors Office

T 30 S R 2 W
¼ $\frac{S \ 22}{S \ 27}$
1968

All BTs OK and tagged.

Fd. OK, May 1990 by D. Bentz - M 110-16

Fd. OK, Oct. 1996 by K.DeGroot - M 125-80