

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 440340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 22

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Survey by Kristian DeGroot - For: John and Marion Liming -
oct. 1996 - M 125-80

Set a 5/8" x 30" Iron rod 28" in the ground with a plastic
cap "BTS Eng. Surv.", from which new bearing trees:

A 8" D.Fir bears N.14°E., 33.6 ft. scribed C¼ S22 BT.

A 12" Madrona bears N.65°W., 31.8 ft. scribed C¼ S22 BT
and new bearing objects:

A 5/8" x 30" Iron rod with plastic cap "BTS Eng. Surv."
bears N.82°E., 18.35 ft.

A 5/8" x 30" Iron rod with plastic cap "BTS Eng. Surv."
bears S.38°W., 15.15 ft.

All new bearing trees have double blazed faces with a brass
washer stamped "PLS 1941" nailed into the lower blaze.
Bearings are taken to the center of the tree at the root
crown and distances measured to a nail in the root crown at
the side and center of the tree.