

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 10 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6829)

Set a conglomerate stone 14x12x6 ins., 9½" in the ground for ¼ sec. cor. on S. bdy. Sec. 10, marked ¼ on N. face, from which

A Madrone 7" dia., bears N.69°E., 34 lks. dist. mkd. ¼ S10 BT.

A Cedar 9" dia., bears N.40°W., 55 lks. dist. mkd. ¼ S10 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-8

Found - 14x12x6" stone mkd. ¼.
9" Cedar, now stob, N.40°W., 36.3 ft., tree opened, "BT" visible.
7" Laurel, now burnt stump, N.69°E., 22.4 ft., shows burnt face.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 10
1968

New BTs- 6" D.Fir N.27°E., 3.2 ft. scribed ¼ S10 CS BT.

8" D.Fir N.27°W., 45.8 ft. mkd. ¼ S10 CS BT.

Corner lies 15.0 ft. South of E-W fence line.

Tony Hostetter - For: Seneca Jones Timber Co. & Roseburg Resources Co. - April 2011 - M162-29

Found - 1968 brass cap as set by Douglas County Surveyors Office (C.S. 54/73), from which:

20" Fir, face evident, BLM tag, N.27°E., 3.2 ft.

17" Fir, face evident, BLM tag N.27°W., 45.8 ft.

New BTs- 8" madrone, scribed "S10 ¼ BT", N.72°57'E, 23.9 ft to spike.

10" madrone, scribed "S10 ¼ BT" S.12°38'E, 24.3 ft to spike.