

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 3 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6199) (Duplicate pg. 6823)

Set a basalt stone 18x6x6 ins., 12" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Fir 12" dia., bears N.25°W., 54 lks. dist. mkd. ¼ S34 BT.
A Fir 18" dia., bears S.1°W., 48 lks. dist. mkd. ¼ S3 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6217)

Intersect the ¼ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 3, T30S R2W only by destroying all marks referring to sec. 34 and marking ¼ on S. face, from cor.
A Fir 18" dia., bears S.1°W., 48 lks. dist. mkd. ¼ S3 BT. (Old BT)
A Fir 14" dia., bears S.25°W., 45 lks. dist. mkd. ¼ S3 BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 26, 1968 - C.S. File 54/73-50

Found - Stone at corner approx. size, mkd. ¼ on N. side.
18" now 30" R.Fir, S.1°E., (Rec. S.1°W) 31.7 ft., shows good scar.
14" now 20" R.Fir S.25°W., 29.7 ft., shows good scar
Record distance of 26.4 ft. East of ¼ sec. 34, T29-2
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S
T 30 S R2W ¼ _____
1968 S 3

All bearing trees OK and tagged.