

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 478500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14 & 15 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6762)

Set post cor. secs. 10, 11, 14 and 15, from which
A Pine 30" dia., bears S.74°W., 25 lks.
A Pine 18" dia., bears N.15°W., 54 lks.
A Fir 10" dia., bears S.88°E., 180 lks.
A Laurel 4" dia., bears N.60°E., 61 lks.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6798 and 6828-29)

(Page 6798)
The cor. of secs. 10, 11, 14 and 15, nearly obliterated. The only evidence of this cor. are the SW. bearing tree and the dead stump of the NW. bearing tree.
(Page 6828-29)
I re-establish the old cor. of secs. 10, 11, 14 and 15 in its original position as the cor. of secs. 14 and 15 only, as follows:
Set a conglomerate stone 15x12x8 ins., 10" in the ground, marked with 4 notches on S. and 2 notches on E. edge, from which
A Fir 18" dia., bears S.48½°E., 86 lks. dist. mkd. T30S R2W S14 BT.
A Yellow Pine 36" dia., bears S.74°W., 27 lks. dist. mkd. T30S R2W S15 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - April 29, 1959 - C.S. File 42/421-6

Determined by O.B.T.s:
40" Pine stump, logged, bears S.74°W., 17.8 ft. found scribe.
32" Fir S.48°E., 56.7 ft.
At corner point, found stone and SET 1" x 30" Iron rod, from which
12" Maple bears S.55°W., 66.0 ft., slope dist., mkd. S15 X BT.
8' x 8' x 15' high rock out crop, bears S.48°W., 68.0 ft., slope dist.
6" Fir N.56°W., 8.5 ft. mkd. S10 R2W BT.
6" Fir N.63°E., 13.3 ft. mkd. S10 T30S BT.
5" Laurel S.60°E., 32.5 ft. mkd. S14 T30S R2W BT.
Sec. Corner for 10 and 11 bears East 115.0 ft. distance.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 14 & 15 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13417-18)

 The cor. of secs. 14 and 15 only, on the S. bdy. of sec. 10, monumented with a conglomerate stone, 15x12x8 ins., firmly set 12" in the ground, mkd. with 4 notches on S. and 2 notches on E edges, from which the remains of an original BT:
 A sawed Yellow Pine stump 36" dia., bears S.74°W., 28 lks. dist., with blaze face burned out. (Mensch record dist., 27 lks.)

and a tree mkd. by Mensch in 1909:
 A sawed Fir stump 30" dia., bears S.47½°E., 85 lks. dist. mkd. with a well healed blaze. (Rec. brg. & dist., S.48½°E., 86 lks.)

and trees mkd. by Markham in 1959:
 A Fir 10" dia., bears N.65½°E., 20 lks. dist., with illegible scribing on an open blaze.
 A Madrone 6" dia., bears S.59½°E., 48 lks. dist., with illegible bark scribing sloughed off.
 A Maple 12" dia., bears S.55°W., 87 lks. dist., mkd. S15 X BT on open blaze. Reblazed and mkd. T30S R2W S15 BT.
 A Fir 8" dia., bears N.57½°W., 12 lks. dist., with illegible scribe marks on a double blaze.

At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:
 T 30 S R 2 W
 S 10
 S 15 | S 14
 1963

from which a new bearing tree:
 A Fir 5" dia., bears S.64½°E., 37 lks. dist., mkd. T30S R2W S14 BT.
 Deposit the conglomerate stone alongside the iron post.

Fd BC & 4 BTs, by T. Hostetter 4/2011 - M162-29

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22649-50)

 The cor. of secs. 14 and 15 only, bears N.88°40'01"W., 114.92 ft. (from the S Cor Secs. 10 & 11).., monumented with an iron post, 2½" dia., firmly set, projecting 8". above ground, (alongside of which is an iron rod, 1" dia., firmly set, projecting 10" above ground) with brass cap (properly) mkd.
 continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 478500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14 & 15 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an orig. bearing tree
A sawed pine stump, 37" dia., bears S.74°W., 18.5 ft.,
with no marks visible.
and the remains of a bearing tree mkd. by Mensch in 1909
A sawed fir stump, 28" dia., bears S.47½°E., 56.1 ft.,
with a healed blaze.
and bearing trees mkd. by Markham, Jr., in 1959
A fir, 13" dia., bears N.65½°E., 13.2 ft., with a healed
double blaze.
A madrone, 10" dia., bears S.59½°E., 31.7 ft., with no
marks visible.
A maple, 14" dia., bears S.55°W., 57.4 ft., with no marks
visible on a partially opened blaze.
and a bearing tree mkd. by White
A fir, 11" dia., bears S.64½°E., 24.4 ft., with a healed
blaze.

Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72

Found - 3" brass cap
3" brass cap secs 10 & 11 only bears S.88°37'13"E.,
114.99'
37" sawed pine stump, S.74°W., 18.5', no marks
28" Sawed fir stump, S.47½°E., 56.1'
23" Fir N.65½°E., 13.2' healed double blaze.
19" Madrone, S.59½°E., 31.7', no marks
21" Maple S.55°W., 57.4' partially open scar, no
marks.
21" Fir, S.64½°E., 24.4' healed blaze.