

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6216)

-----  
Set a basalt stone 18x12x4 ins., 12" in the ground for cor. of secs. 34 and 35, marked with 2 notches on E. and 4 notches on W. edge; from which  
A Fir 24" dia., bears N.32°30'E., 57 lks. dist., mkd. T29S R2W S35 BT.  
A Fir 40" dia., bears N.12°30'W., 47 lks. dist. mkd. T29S R2W S34 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-48

-----  
Found - Stone at sec. cor. mkd. 2 notches on E. & W.  
40" now 45" D.Fir N.12½°W., 31.0 ft. shows good scar.  
24" Fir now stob, N.32½°E., 37.6 ft. scribe visible.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R2W S 34 | S 35  
T 30 S 1968 S 3  
New BTs- 16" Hemlock N.8°E., 26.6 ft. mkd. T29S R2W S35 CS BT  
14" Hemlock S.51½°W., 33.9 ft. mkd. T30S R2W S3 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 2/10/98 - C.S. File 64/79-27

-----  
Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, protrudes 13" above ground. 1968  
18"x12"x4" stone found loose on top of ground 2 ft. West of BC/IP. Stone is marked on two sides, 2 hashes on one side and 4 on its opposite. Orig. stone.  
40" now 44" dia., 2 ft. high D.Fir stump, bears N.12½°W., 31.0 ft. (Agrees with rec.) OBT Orig. NE BT now gone.  
16" now 17" dia., 3 ft. high Hemlock stump with scribing visible on a partially healed blaze "35 CS" bears N.8°E., 26.6 ft. (Agrees with rec.) 1968  
1968 SW BT gone.  
DCSO BC/IP mkd: T29S R2W S35/S3 | S2 T30S bears East 32.0 ft. (Rec. East 33.7 ft.)  
Set - Stone placed loose along west edge of BC/IP.  
(Cont. next page)

