

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6759)

Set ¼ sec. post, from which
A Pine 15" dia., bears S.6°W., 290 lks.
A Pine 15" dia., bears S.15°E., 215 lks.

Douglas Co. Surveyors Office - L.E. Monrean; R.B. Kimberling, crew - May 3, 1977 - C.S. File 59/34-4

Found - 3" x 3" Fir post laying down, not of record, 4.0 ft. South, 0.5 ft. East of corner as set from BT.
A Pine log and stump bears S.15°E., 141.9 ft. with fragmentary scribing at top of blaze "1/", appears to be portion of 1/4.
Remains of Pine stump with previously opened blaze, bears ~~S~~.5°30'W*. , 186.9 ft. but exact orig. standing place not determined.

Both BTs are in small creek.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
1/4 S34|S35
1977

at record bearing and distance from only BT.

New BTs- A 27" D.Fir bears S.57½°E., 46.0 ft. double blazed and scribed "¼ S35 CS BT".

A 12" D.Fir bears S.41°W., 7.5 ft. double blazed and scribed "¼ S34 CS BT".

*Correction made 5/31/2016, JC DCSO

Fd. OK, July 1994 by G. Lang - M 120-69

Jonathan B. Drew, II, USFS - Reported by: Andrew Hillman & Assisted by: Jacob Hunt - 8/26/2016 - C.S. File 65/93-52

Found - A 1¼" galv. iron pipe with a 2½" brass cap, (properly mkd) projecting 12" above the ground.
No trace fd of a (15" pine) 1857, (S.6°W., 191.4') 1857, S.5°30'W., 186.9') 1977
No trace found of a (15" pine) 1857, (S.15°E., 141.9 ft) 1857 & 1977
A 33" fir with a healed single blaze, (S.57°30'E., 46.0 ft) 1977
A 17" fir with a healed single blaze, (S.41°W., 7.5 ft) 1977
No new accessories added.

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.
Lat: N.42°55'26.109" Long: W.122°55'21.309"
Datum: NAD83
Source: Post processed resource grade, as reported by Jack Snyder.