

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6760)

- 
- Set post cor. secs. 22, 23, 26 and 27, from which
- A Laurel 10" dia., bears S.15°W., 25 lks.
  - A Laurel 10" dia., bears N.50°E., 53 lks.
  - A Sugar Pine 60" dia., bears N.73°W., 133 lks.
  - A Fir 6" dia., bears S.28°E., 44 lks.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson; Loren Weber - Aug. 2, 1940 - C.S. File 16/55

- 
- Location identified from original bearing tree:
- A 24" Fir S.28°E., 44 lks., chopped out, scribe marks partially legible.
  - A 60" Pine, down and burned. Checks original bearing and distance.
- Drove 1½" x 60" angle iron, 50" in ground for corner and surrounded with a mound, from which
- A Fir 20" dia., bears S.60°W., 19 lks. mkd. T30S R2W S27 CS BT.
  - A Fir 8" dia., bears S.27°E., 53 lks. mkd. T30S R2W S26 CS BT.
  - A Fir 22" dia., bears N.12°W., 37 lks. mkd. T30S R2W S22 CS BT.
  - A Fir 24" dia., bears N.15°E., 38 lks. mkd. T30S R2W S23 CS BT.

Cor. Fd. July 1959, DCSO, C.S. File 16/55

- 22" Fir should be N.4°W., 24.4 ft.
- 24" Fir should be N.20°E., 25.1 ft.

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13409-10)

- 
- The Sec. Cor., perpetuated by Irving in 1940, with an angle iron 1½" x 1½"., 51" long, firmly set 46" in the ground, from which the remaining original bearing trees:
- A Fir 28" dia., bears S.33°E., 46 lks. dist. mkd. with a decayed and burned blaze. (Rec. bearing and distance, S.28°E., 44 lks.)
  - A Madrone 17" dia., bears S.15°W., 25 lks. dist. with blaze completely healed.
- and trees mkd. by Irving:
- A Fir 32" dia., bears N.21°E., 40 lks. dist. mkd. T30S R2W CS BT, on bark blaze.
- (Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A Fir 12" dia., bears S.25½°E., 54 lks. dist., mkd. with a healed blaze.

A Fir 21" dia., bears S.58°W., 20 lks. dist. mkd. T30S R2W S27 CS BT, on bark blaze.

A Fir 30" dia., bears N.3°W., 38 lks. mkd. T30S R2W S22 CS BT, on bark blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:

T 30 S R 2 W  
S 22 S 23  
S 27 S 26  
1963

Deposit angle iron alongside the iron post.