

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6761-62)

Marked an Oak 6" dia., cor. secs. 14, 15, 22 and 23, from which

- A Fir 10" dia., bears S.45°W., 7 lks.
- A Fir 36" dia., bears N.74°E., 25 lks.
- A Fir 10" dia., bears S.10°E., 27 lks.
- A Laurel 10" dia., bears N.45°W., 45 lks.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6799 and 6812)

(Page 6799)

The Cor. of secs. 14, 15, 22 and 23, nearly obliterated. The Cor. tree and NW. bearing tree are dead and fallen. The other bearing trees are deeply overgrown.

(Page 6812)

The Sec. cor., which I re-establish in its original position as follows:

I uproot the dead and decayed cor. tree and set a conglomerate stone 16x10x8 ins., 11" in the ground, marked with 3 notches on S. and 2 notches on E. edge, from which

- A Fir 36" dia., bears N.74°E., 27 lks. dist. mkd. T30S R2W S14 BT.
- A Fir 12" dia., bears S.10°E., 28 lks. dist. mkd. T30S R2W S23 BT.
- A Fir 10" dia., bears S.45°W., 8 lks. dist. mkd. T30S R2W S22 BT.
- A Fir 8" dia., bears N.85°W., 22 lks. dist. mkd. T30S R2W S15 BT.

John H. Markham, Jr. R.E. #2880 - June 24, 1949 - C.S. File 40/185

At corner point, found original stone beside which I drove a 1/2" x 24" Iron pipe. A fence runs North and East from this corner. Original BTs all in good condition viz:

- Fir N.74°E., 23.0 ft.
- Fir S.10°E., 18.5 ft.
- Fir S.45°W., 5.2 ft.
- Fir N.85°W., 14.5 ft.

"This cor. in slide area. Unable to fix true position of corner" - June 5, 1963 - J.W. Byron

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13413-14)

 Point for the cor. of secs. 14, 15, 22 and 23, at record distance in latitude South of the ¼ sec. cor. of secs. 14 and 15, and record distance in departure East of the corner of secs. 15, 16, 21 and 22, based on the 1909 resurvey by Mensch.

At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 30 S R 2 W			
S 15	S 14		
S 22	S 23		
1963			

from which

A Fir 5" dia., bears N.32½°E., 40 lks. dist., mkd. T30S R2W S14 BT.

The NW. face of a rock ledge, 11x9x7 ft. above ground, bears S.70½°E., 23 lks. dist., mkd. B X 0.

The NE. corner of a rock ledge, 36 x 21 x 7 ft. above ground, bears S.44½°W., 64 lks. dist. mkd. B X 0.

No trees or objects available in section 15.

From this point, the corner monument set by Mensch in 1909 at the sec. cor., bears S.87°06'E., 1.58 chs. dist., a granite stone 15 x 13 x 9 ins., lying loose on the ground, mkd. with 2 grooves on E. and 2 grooves on S. sides, from which the original bearing trees mkd. by Hathorn:

A rotted Fir stump and snag, 36" dia., bears N.74°E., 25 lks. dist., mkd. T, and other illegible scribing on pitched-over blaze. (Mensch record dist. 27 lks.)

A Fir 12" dia., bears S.12½°E., 28 lks. dist. mkd. with illegible scribing on a partially opened blaze. (Mensch record bearing and dist. S.10°E., 28 lks.)

A fallen Fir 15" dia., bears S.45°W., 8 lks. dist., mkd. with illegible scribing on a partially opened blaze.

and a tree mkd. by Mensch:

A Fir 12" dia., bears N.75½°W., 27 lks. dist., mkd. T30S R2W S, on opened blaze. (Rec. brg. & dist. N.85°W., 22 lks.)

This corner monument has been moved from its original geographic position by a massive earth slide and settling of the earth's surface, in February 1962. The area is locally known as the "Dompier Creek Slide." Ground conditions indicate, and local residents verify, that the earth in this area has been forced upward and to the East, by the slide.

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec Cor. for 14, 15, 22 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. OK, Oct. 1996 by K. DeGroot - M 125-80
Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72 ----- Found - 3" brass cap NW Corner of rock ledge, 11'x9'x7', above ground & marked "BX0" bears S.70°30'E., 15.2' NW Corner of rock ledge, 36'x21'x7' above ground & marked "BX0" bears S.44°30'W., 42.2'