

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10 & 11 only (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6804)

Set a conglomerate stone 14x12x8 ins., 9½" in the ground for cor. of secs. 10 and 11, marked with 2 notches on E. edge, from which

A Fir 24" dia., bears N.84°E., 7 lks. dist. mkd. T30S R2W S11 BT.

A Fir 15" dia., bears N.14½°W., 75 lks. dist. mkd. T30S R2W S10 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - April 29, 1959 - C.S. File 42/421-7

Determined by O.B.T.s:

32" Fir uproot bears N.84°E., 4.6 ft., found scribe.

30" Fir N.14°W., 51.5 ft.

At corner point, found stone and SET ¾" x 30" Iron pipe, from which

4" Laurel bears N.43°W., 19.4 ft. mkd. S10 T30S R2W BT.

11" Fir bears N.33°E., 13.0 ft. S11 BT.

11" Laurel bears N.53°E., 33.0 ft. mkd. S11 T30S R2W BT.

8" Fir bears S.57°E., 25.0 ft. mkd. S1041 BT.

Sec. Cor. for 14 and 15 bears West 115.0 ft. dist.

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13418)

The cor. of secs. 10 and 11 only, on the N. bdy. of sec. 14, monumented with the original conglomerate stone, 12x9x7 ins., firmly set 7" in the ground, mkd. with 2 notches on E. edge and a cross (X) on top, from which the original bearing trees:

A fallen Fir 27" dia., bears N.84°E., 7 lks. dist., with partial scribe marks visible on an opened blaze.

A Fir 28" dia., bears N.14½°W., 76 lks. dist. with illegible scribe marks visible on a partially opened blaze. (Record dist., 75 lks.)

and trees mkd. by Markham in 1959:

A Fir 14" dia., bears N.29¼°E., 19 lks. dist. mkd. S11 BT on open blaze. Reblazed and marked T30S R2W S11 BT.

A Madrone 10" dia., bears N.53°E., 50 lks. dist., mkd. S11 T30S R2W BT, in the bark.

A Fir 10" dia., bears S.55°E., 38 lks. dist., with illegible scribing on a partially healed blaze.

(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10 & 11 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Madrone 6" dia., bears N.45°W., 30 lks. dist., mkd. S10 T30S R2W BT, in the bark.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 9" in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd:

T 30 S R 2 W
S 10 | S 11
S 14
1963

Deposit original stone alongside the iron post.

Fd BC & 4 BTs, by T. Hostetter 4/2011 - M162-29

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22648-9)

The cor. of secs. 10 and 11 only, monumented with an iron post, 2½" dia., firmly set, projecting 1" above a mound of stone, 3½ ft. dia., 2 ft. high, (alongside of which is an iron pipe, ¾" dia., loosely set, projecting 10" above the mound of stone), with brass cap (properly) mkd.

from which the remains of the orig. bearing trees

A decayed and partially uprooted fir stump, size indeterminate, bears N.84°E., 4.6 ft., with no marks visible.

A fir, 31" dia., bears N.14½°W., 50.2 ft., with a healed double blaze.

and the remains of BTs mkd. by Markham, in 1959

A fir, 19" dia., bears N.29¼°E., 12.5 ft., with a healed blaze.

A madrone, 13" dia., bears N.53°E., 33.0 ft., with no marks visible.

A fir snag, 11" dia., bears S.55°E., 25.1 ft., with illegible scribe marks visible on an open blaze.

A madrone, 7" dia., bears N.45°W., 19.8 ft., with no marks visible.

From this cor., the cor. of secs. 14 and 15 only, bears N.88°40'01"W., 114.92 ft.

Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72

Found - 2.5" brass cap

3" brass cap, secs 14 & 15 only, bears N.88°37'13"W. 114.99'

33" Fir, N.14½°W., 50.2', healed double blaze.

11" Fir snag, S.55°E., 25.1'

22" Fir N.29¼°E., 12.5'

Continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10 & 11 only (South)

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - 12" Madrone, N.45°W., 19.8', no visible marks 5' steel post, set 4' east.