

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6839-40)

-----  
Set a basalt stone 15x8x8 ins., 10" in the ground, for ¼ sec. cor. mkd. ¼ on W. face, from which  
A Fir 40" dia., bears S.47°E., 29 lks., mkd. ¼ S11 BT.  
A Fir 9" dia., bears N.27°W., 32 lks., mkd. ¼ S10 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley - Feb. 1960 - C.S. File 42/421-13

-----  
Determined by O.B.T.s:  
15" W.Fir snag, N.29°W., 21.3 ft.  
45" Fir, uproot, S.47°E., 19.1 ft., found scribe.  
At corner point, found stone and SET 1½" x 30" Iron pipe, from which  
7" W.Fir bears S.18°W., 34.0 ft. mkd. ¼ S10 BT.  
11" W.Fir bears S.33°E., 44.7 ft. mkd. ¼ S11 BT.  
4" Cedar bears S.75°E., 25.7 ft. mkd. ¼ S11 BT.  
15" Cedar bears N.11°W., 41.0 ft. mkd. ¼ S10 BT.  
Road bears South 450.0 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22648-9) (added 10/2011)

-----  
The ¼ sec. cor. of secs. 10 and 11, perpetuated by Markham, Jr., in 1960, monumented with an iron pipe, 30" long, 1½" dia. firmly set, projecting 9" above ground, with a threaded and smashed top, (alongside of which is the orig. basalt stone, 8x8x15" firmly set, projecting 4" above ground, mkd. ¼ on W. face, with a cross chiseled on top) from which the remains of an orig. bearing tree  
A roothole bears S.47°E., 19.1 ft., alongside of which is an uprooted fir stump, size indeterminate, with no marks visible  
and the remains of bearing trees mkd. by Markham, Jr.  
A cedar, 19" dia., bears S.75¼°E., 26.0 ft., with no marks visible.  
A fir snag, size indeterminate, bears S.33°E., 44.4 ft., with no marks visible.  
A fir, 24" dia., bears S.17¾°W., 33.5 ft., with a healed blaze.  
A cedar snag, 16" dia., bears N.11°W., 41.2 ft., with scribe marks S 10 visible on an open, weathered blaze.  
At the corner point

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T30S R2W

¼

S 10 | S 11

2009

from which

A fir, 10" dia., bears S.89¼°E., 32.7 ft., mkd. ¼ S11 BT. Bury orig. stone alongside, place iron pipe inside, and deposit a magnet in a white plastic case at the base of the stainless steel post.

Tony Hostetter - For: Seneca Jones Timber Co. & Roseburg Resources Co. - April 2011 - M162-29

Found - 2010 BC (Not yet of record)

11" Fir, scribing visible, 2010 BLM BT, S.89°E., 32.7 ft.

19" Cedar, face evident, 1960 BT, S.75°E., 25.7 ft.

24" W.Fir, face evident, 1960 BT, S.18°W., 34.0 ft.

17" Cedar snag, face evident 1960 BT N.11°W. 41.0 ft