

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6842)

Set a basalt stone 15x8x6 ins., 10" in the ground, for ¼ sec. cor., marked ¼ on W. face, from which
A Yew 5" dia., bears N.34°E., 10 lks. dist. mkd. ¼ S2 BT
A Hemlock 6" dia., bears S.70°W., 29 lks. dist. mkd. ¼ S3 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - W. Penley; J. Heritage - Aug. 9, 1971 - C.S. File 54/73-77

Found - Orig. stone at corner as recorded.
5" Yewwood now 6", N.34°E., 6.6 ft. shows old scars.
Faces rotted, no scribing found.
6" Hemlock now 15", S.75°W., not S.70°W., 19.2 ft.
We open and find good scribe marks.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S3|S2
1971
New BT - 22" D.Fir bears N.63°E., 10.8 ft. scribed ¼ S2 CS BT

David Edwards - Crew: Brant Miller & Eric Sprinkle - 2/13/2017 - C.S. File 65/95-26

Found - 1971 DCS Brass Capped iron pipe in good condition.
Orig. BT, a 7" dia. Yew with axed face bears N.34°E., 6.6 ft.
Orig. Hemlock in Sec. 3 is a blowdown.
1971 DCS BT, a 22" dia. high stumped Fir bears N.63°E., 10.8 ft.
Scribing visible on partially healed blaze.
New - A 5" dia. Fir scribed "¼ S3 BT" bears S.33°W., 11.0 ft.
A six foot steel post is set 2 feet North.
Compass Declination 15° East