

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3 only (North)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6198) (Duplicate pg. 6822)

Set a basalt stone 15x10x8 ins., 10" in the ground for cor. of secs. 2, 3, 34 and 35, marked with 2 notches on E. and 4 notches on W. edge, from which

A Fir 15" dia., bears N.72°E., 22 lks. dist. mkd. T29S R2W S35 BT.

A Fir 6" dia., bears S.32 3/4°E., 23 lks. dist. mkd. T30S R2W S2 BT.

A Fir 10" dia., bears S.66½°W., 23 lks. dist. mkd. T30S R2W S3 BT.

A Fir 6" dia., bears N.68°W., 49 lks. dist. mkd. T29S R2W S34 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6216)

Intersect the cor. of secs. 2, 3, 34 and 35, which is a basalt stone firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 2 and 3, T30S R2W only by destroying all marks referring to secs. 34 and 35, from cor.

A Fir 6" dia., bears S.32°45'E., 23 lks. dist. mkd. T30S R2W S2 BT. (Old BT)

A Fir 10" dia., bears S.66°30'W., 23 lks. dist. mkd. T30S R2W S3 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-49

Found - Stone at cor. mkd. + on top, record dist. 33.7 ft. E. of sec. cor. 34 & 35, T29-2.
 10" now 26" R.Fir S.66½°W., 15.2 ft., shows good scar.
 6" Fir now down and laying on face, S.32 3/4°E., 15.2 ft.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S	S 35
T 30 S R2W	S 3 S 2

1968

New BTs- 7" D.Fir S.71°E., 26.5 ft. mkd. T30S R2W CS BT.
 12" Hemlock N.14°E., 13.6 ft. mkd. T29S R2W S35 CS BT.

(Cont. next page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs. 2 & 3 - North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 2/10/98 - C.S. File 64/79-29

Found - 2½" dia., brass cap on a 1½" O.D. iron pipe, flush with the ground, leans 1 ft. East. 1968
12"x8"x6" stone is found loose on top of ground, along West edge of BC/IP. Stone is marked with a "+". Orig. stone.
10" now 22" dia., 3½" high Fir stump, previously opened, unhealed, no scribing visible, bears S.66½°W., 13.9 ft. (Rec. S.66½°W., 15.2') OBT
12" now 12" dia. 3 ft. high Hemlock stump with an unhealed double blaze scribing visible "T29S R2W S35 CS BT" bears N.17°E., 13.6 ft. (Rec. N.14°E., 13.6') 1968
7" now 17" dia. D.Fir with a fully healed double blaze, bears S.71°E., 27.5 ft. (Rec. S.71°E., 26.5 ft.) 1968
DCSO 1968 BC/IP mkd: "T29S R2W S34|S35/S3" bears West 32.0 ft. (Rec West 33.7 ft.)
Set - BC/IP returned to plumb position, flush with the ground. Stone is loose along W. edge of BC/IP.
8" dia. D.Fir, double blazed and scribed "T30S R2W S3 CS BT", bears S.62°W., 22.2 ft.
Metal caps are on BT stumps.
See sketch in file.