

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 538500

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6763)

Set ¼ sec. post, from which
A Fir 40" dia., bears N.5°E., 13 lks.
A Fir 12" dia., bears S.85°W., 51 lks.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6798 and 6803-04)

(Page 6798)
The ¼ sec. cor. is about entirely obliterated. The only tree being the fallen body of the NW. bearing tree.
(Pages 6803-04)
I re-establish the old ¼ sec. cor. in its original position as the ¼ sec. cor. on N. bdy. sec. 14 only, as follows:
Set a porphyry stone 15x8x6 ins., 10" in the ground for ¼ sec. cor., marked ¼ on S. face, from which
A Fir 5" dia., bears S.54°E., 28 lks. dist. mkd. ¼ S14 BT.
A Fir 6" dia., bears S.26½°W., 63 lks. dist. mkd. ¼ S14 BT

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - April 28, 1959 - C.S. File 42/421-1

Determined by O.B.T.:
18" Fir bears S.26°W., 51.0 ft., slope dist., found scribe
At corner point, found stone and SET 3/4" x 40" Iron rod, from which
14" Laurel bears S.17°E., 34.6 ft. mkd. ¼ S14 T30S R2W BT
3" Chinquapin bears S.19°W., 11.5 ft. mkd. ¼ S BT.
7" Laurel bears N.89°W., 19.3 ft. mkd. ¼ S14 BT.
4" Fir bears N.49°W., 16.8 ft. mkd. ¼ S11 BT.
So. 1/4 Cor. Sec. 11 bears East 116.0 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22662-3)

The ¼ sec. cor. of sec. 14 only, perpetuated by Markham, Jr., in 1959, bears N.89°24'49"W., 116.03 ft., (from the S¼ S11 only) monumented with an iron rod, 40" long, 3/4" dia., firmly set, projecting 9" above ground, (alongside of which is the stone set by Mensch in 1909, 6x9x12" (Record, 15x8x6"), with marks ¼ visible on N. face and cross on top, from which the remains of a bearing tree mkd. by Mensch
A sawed fir stump, 23" diam., bears S.26½°W., 41.6 ft. with a healed blaze.

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 538500

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 14 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Markham, Jr.
A madrone, 15" diam., bears S.15¾°E., 34.6 ft., with no marks visible.
A forked fir, 8" diam., bears N.47°W., 16.9 ft., with a healed blaze.
At the corner point
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd. T30S R2W
¼ S14
2009
Bury the iron pipe inside, Mensch's stone alongside, and deposit a magnet in a white plastic case at the base of the stainless steel post.

Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72

Found - 2.5" brass cap
49" Fir (no record) N.11°W., 20.5', illegible tree tag, no scar.
17" Madrone, S.15¾°E., 34.6', no visible marks, metal tag.
9" Fir, N.47°W., 16.9', healed scar, metal tag.
New - 14" D.Fir S.7°E., 18.0', scribed "¼ S14 BT"
12" D.Fir S.45°W., 15.5', scribed "¼ S14 BT"