TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35; and S.2, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6754)

Set ¼ sec. post, from which
An Oak 18" dia., bears S.30°E., 132 lks.
A Pine 30" dia., bears N.75°E., 85 lks.

Douglas Co. Surveyors Office - John M. Powell & crew - Aug. 16, 1966 - C.S. File 54/28-82

Found - 30" Pine now 34", N.80°E., 56.1 ft. (posted N.75°E.), scribed "¼S" visible.
18" now 32" Oak S.30°E., 87.1 ft., scribe visible "¼S".

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 35 / S 2

Reblazed and rescribed:
32" Oak S.30°E., 87.1 ft. scribed "¼ S2 CS BT".

Fd. Ok by Glenn Baughman, March 1978 - M65-68

Jonathan B. Drew, II, USFS - Reported by: Andrew Hellman & Assisted by: Jacob Hunt - 8/30/2016 - C.S. File 65/93-43

Found - A 1¼" galv. iron pipe with a 2½" brass cap, leaning slightly to the east and projecting 14" above the ground.
A 42" oak with a healed single blaze, (S.30°E., 87.1 ft) 1857
A 37" pine with a healed single blaze, (N.75°E., 56.1 ft) 1857, (N.80°E.) 1966
No new accessories added.

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.