

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6760)

-----  
Set ¼ sec. post, from which  
    A Fir 18" dia., bears S.E., 3 lks.  
    A Maple 10" dia., bears N., 8 lks.

Glenn Baughman - For: U.S. Forest Service - Feb. 1978 -  
M 65-56

-----  
Found - 14" D.Fir, orig., bears S.45°W., 2.0 ft., down and rotted.  
Set 2" x 30" I.P. with brass cap stamped "T30S R2W WM 1/4 S26 S35 1978 OLS 536".  
New BTs- 26" D.Fir bears N.70°E., 21.5 ft. scribed ¼ S26 BT.  
          8" D.Fir bears S.3°W., 18.8 ft. scribed ¼ S35 BT.

Jonathan B. Drew, II, USFS - Reported by: Jacob Hunt -  
8/17/2016 - C.S. File 65/93-53

-----  
Found - A 2½" galvanized iron pipe with a 3" brass cap (properly mkd), projecting 3" above the ground.  
No trace found of a (18" fir)1857, (southeast - 2.0 ft) 1857, (S.45°W.)1978  
No trace found of a (10" maple)1857, (North - 5.3 ft) 1857  
A 39" fir with a healed single blaze, (N.70°E., 21.2 ft) 1978  
A 15" fir with a healed double blaze, (S.3°W., 18.8 ft) 1978  
Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height.  
Lat: N.42°55'53.173" Long: W.122°54'45.822"  
Datum: WGS84  
Source: USGS Quad map, for navigation to corner.