

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6761)

Set ¼ sec. post, from which
A Fir 18" dia., bears N.2°E., 25 lks.
A Fir 24" dia., bears S.3°E., 30 lks.

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13409)

The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:

A Fir 31" dia., bears N.2°E., 25 lks. dist., opened to reveal the marks BT.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

¼ $\frac{S\ 23}{S\ 26}$
T 30 S R 2 W
1963

from which a new bearing tree:

A Fir 10" dia., bears S.44¼°E., 151 lks. dist., mkd. ¼ S26 BT.

Loyd R. Moffit, LS #944 - For: U.S. Forest Service - Oct. 1986 - C.S. File 62/30-12

Found - 1963 BLM 1" galv. iron pipe with a 3" brass cap.
32" Fir stump, N.06°E., 16.5 ft., scribe visible.
16" Fir bears S.44¼°E., 99.6 ft., scar visible.
New BT - I scribed an 8" Fir which bears N.17°W., 30.8 ft. mkd. "¼ S23 BT" with "LS 944" brass washer nailed to BT scribe.