TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6762)

Set ¼ sec. post, from which
A Fir 15" dia., bears S.40°E., 23 lks.
A Laurel 6" dia., bears N.45°W., 45 lks.

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13415)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 12" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

¼ S 14 / S 23
T 30 S R 2 W
1963

from which
A Fir 38" dia., bears N.62¼°E., 110 lks. dist. mkd. ¼ S14 BT.
A Fir 18" dia., bears S.39½°E., 51 lks. dist., mkd. ¼ S23 BT.

Found OK by R. Brown, Feb. 2001 - M137-42

Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72

Found - 3" brass cap in stone mound.
46" Fir, N.62¼°E., 72.6', healed blaze.
33" Fir, S.39½°E., 33.7', healed blaze.

Brent Knapp, i.e. engineering - Crew: N. Fromdahl, J. Ogden, and L. Heddens - 9/2022 - C.S. File 65/111-25

Found - Brass Cap in stone mound
46" Fir, N.62¼°E., 72.6', Healed blaze
33" Fir, S.39½°E., 33.7', Healed blaze
New - 15" Fir, N.45°E., 10.1', scribed "¼ S14 BT"
12" Chinquapin, S.15°E., 7.0', scribed "¼ S23 BT"
Note - Compass decl. 15°E.