

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 11 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6803)

-----  
Set a porphyry stone 15x10x4 ins., 10" in the ground for ¼ sec. cor. on S. bdy. sec. 11, marked ¼ on N. face, from which  
A Fir 6" dia., bears N.43°E., 42 lks. dist. mkd. ¼ S11 BT.  
A Fir 36" dia., bears N.50°W., 56 lks. dist. mkd. ¼ S11 BT

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -  
Wit: R.G. Boyd - April 28, 1959 - C.S. File 42/421-8

-----  
Determined by O.B.Ts:  
36" Fir snag, bears N.50°W., 37.0 ft., found scribe.  
15" Fir uproot, bears N.43°E., 27.7 ft.  
At corner point, found stone and SET truck axle with gear up, from which  
5" Fir N.36°E., 5.7 ft. mkd. ¼ S11 X BT.  
20" Laurel N.52°W., 50.8 ft. mkd. ¼ S11 T30S R2W BT.  
5" Fir N.61°W., 6.3 ft. mkd. ¼ S11 BT.  
6" Fir S.26°W., 23.0 ft. mkd. ¼ S14 BT.  
North 1/4 Cor. Sec. 14 bears West 116.0 ft.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22662)

-----  
The ¼ sec. cor. of sec. 11 only, perpetuated by Markham, Jr., in 1959, monumented with an iron axle rod, 40" long, 1¼" dia., firmly set, projecting 12" above ground, with a toothed, iron gear on top, 2½" dia., from which the remains of an orig. bearing tree  
A fir snag, 28" dia., bears N.50°W., 37.0 ft., with scribe marks ¼ S11 BT visible on a partially healed blaze.  
and bearing trees mkd. by Markham, Jr.  
A fir, 14" dia., bears N.40°E., 5.6 ft., with a healed double blaze.  
A fir, 17" dia., bears S.27½°W., 21.2 ft., with a healed double blaze.  
A madrone, 19" dia., bears N.51¾°W., 50.5 ft., with a healed double blaze.

At the corner point  
Set a stainless steel post, 28" long, 2½" dia. 19" in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T30S R2W  
¼ S 11  
2009

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 11 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bury iron axle rod alongside and deposit a magnet in a white plastic case at the base of the stainless steel post.  
From this cor., the ¼ sec. cor. of sec. 14 only, perpetuated by Markham, Jr., in 1959, bears N.89°24'49"W., 116.03 ft.

Fd. as per 2009 BLM rec. by D. Edwards, 3/2017 - M173-14

Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72

-----  
Found - 2.5" brass cap  
15" Fir, N.40°E., 5.6' healed blaze.  
19" Fir, S.27½°W., 21.2' healed blaze.  
5'x28" Fir snag, N.50°W., 37.0' partially healed blaze.  
19" Madrone, N.51¾°W., 50.5' healed double blaze & tag.  
New - 16" D.Fir N.73°W., 12.6' scribed "¼ S11 BT"