

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6841)

-----  
Set a conglomerate stone 15x8x6 ins., 10" in the ground for 1/4 sec. cor., marked 1/4 on N. face, from which  
A Fir 16" dia., bears N.37°W., 33 lks. dist. mkd. 1/4 S2 BT.  
A Fir 24" dia., bears S.61°W., 22 lks. dist. mkd. 1/4 S11 BT

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 15, 1968 - C.S. File 54/73-38

-----  
Found - No trace of stone at 1/4 corner.  
16" D.Fir, now stump, N.37°W., 21.8 ft., opened stump for scribing.  
24" D.Fir, now stump, S.61°W., 14.5 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 30 S R 2 W  
S 2  
S 11  
1968

New BTs- 10" Cedar S.71°W., 17.4 ft. mkd. 1/4 S11 CS BT.  
8" Cedar N.42°W., 20.8 ft. mkd. 1/4 S2 CS BT.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22652-3)

-----  
The 1/4 sec. cor. of secs 2 & 11, perpetuated by the Douglas Co Surveyor's Office, in 1968, monumented with an iron post, 1 1/4" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.

from which the remains of the orig. bearing trees  
A sawed, decayed fir stump, 21" dia., 5 ft. high, bears S.61°W., 14.5 ft., with no marks visible on a decayed, open blaze.

A sawed, decayed fir stump, 26" dia., bears N.37°W., 21.8 ft., with scribe marks S 2 visible on an open blaze.  
and BTs mkd. by the Douglas County Surveyor's Office

A cedar, 14" dia., bears S.71 1/4°W., 17.3 ft., with a healed double blaze.

A cedar, 10" dia., bears N.42 1/2°W., 20.9 ft., with scribe marks S2 CS BT and other fragmentary scribe marks visible on a partially healed blaze.

and a new bearing tree

A fir, 10" dia., bears N.25 3/4°W., 15.5 ft., mkd. 1/4 S2 BT.  
Corner is located on a SE. slope

NAD 1983(CORS) Lat: 42°59'23.36"N Long: 122°54'44.49"W