

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 578500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 14 only, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6758)

Set post cor. sec. 11, 12, 13 and 14, from which
A Laurel 12" dia., bears S.80°E., 16 lks.
A Laurel 12" dia., bears S.85°E., 20 lks.
A Fir 12" dia., bears N.85°W., 73 lks.
A Fir 30" dia., bears S.40°W., 70 lks.

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6798 and 6803)

(Pg. 6798)
The cor. of secs. 11, 12, 13 and 14, nearly obliterated. No trace of the post is found. The bearing trees are all standing but deeply overgrown.
(6803)
I re-establish the old cor. of secs. 11, 12, 13 and 14 in its original position as the cor. of secs. 13 and 14 only, as follows:
Set a porphyry stone 14x8x6 ins., 9½" in the ground for cor. of secs. 13 and 14, marked with 4 notches on S. and 1 notch on E. edge, from which
A Madrone 15" dia., bears S.76½°E., 16 lks. dist. mkd. T30S R2W S13 BT.
A Fir 30" dia., bears S.40°W., 72 lks. dist. mkd. T30S R2W S14 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Jan. 26, 1959 - C.S. File 42/421-5

Determined by O.B.Ts:
15" Laurel stump bears S.76½°E., 10.5 ft., found scribe.
At corner point found large stone and SET ¾" x 40" Iron rod, from which
36" Fir bears S.24°E., 21.0 ft. mkd. S13 BT.
5" Fir bears N.33°E., 9.3 ft. mkd. S11 BT.
12" Laurel bears N.11°E., 10.8 ft. mkd. S11 BT.
9" Laurel bears S.72°W., 64.0 ft. mkd. S14 T30S R2W BT.
SW. Corner sec. 12 bears East 120.0 ft.

Fd. OK, Nov. 1968 by DCSO, J. Powell C.S. 54/73-38A

(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 578500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 14 only (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Jim Landrum, U.S. Forest Service (Deputized by the County) -
L. Herzstein, witness - June 21, 1983 - C.S. File 62/10-13

Found - Orig. corner stone 5" x 8", projecting 4" above
ground firmly set with "+" on top.

1" Iron rod with piece of iron welded on northerly
side, firmly set, projecting 10" above the
ground, set by Markham bears N.60°W., 0.3 ft.
from the "+".

I used "+" on orig. stone as corner point as it doesn't
appear to have been removed by Markham.

Found - Remains of orig. BT, a Madrone root crown, size
indeterminate, bears S.76½°E., 10.5 ft.

1959 BT, a 14" Madrone snag N.11°E., 10.8 ft. with
scribe marks "S11 BT" visible on partially healed
double blaze.

1959 BT, a 12" D.Fir N.33°E., 9.3 ft. with healed
blaze.

1959 BT, a 36" D.Fir stump S.24°E., 21.0 ft. with
scribe marks "S13" visible on partially healed
upper blaze and bark scribes "BT" visible on
lower bark blaze.

1959 BT, a 12" Madrone snag S.72°W., 64.0 ft. with
healed blaze.

Sec. corner to Secs. 11 and 12 only, bears N.87½°E.,
119.0 ft.

I remove 5" x 8" x 14" Original corner stone and in its
place, I SET a 2" Iron post, 30" long, set 28" in the ground
with brass cap mkd. "Douglas County Surveyor T30S R2W S11
S14 S13 1983". 1" x 37" Iron rod was buried inside iron
post. Orig. corner stone was buried alongside.

New BTs- 12" D.Fir S.10°E., 28.8 ft. scribed "T30S R2W S13 CS
BT" on a single blaze. Base of blaze is 2 ft.
above ground.

8" D.Fir S.15½°W., 30.8 ft. scribed "T30S R2W S14 CS
BT" on a single blaze.

Steel fence post set with U.S.F.S. signs #54-2 and 54-4
attached bears South 1.8 ft. causing the local attraction.
Scribe marks by Markham are marked starting from bottom to
top.

Found OK by B. Shaner, Mar. 2001 - M132-75 & CS65/36-12A

Ron Quimby - Crew: N. Fromdahl & R Heichel - 11/2017 - C.S.
File 65/99-31

Condition report only

Found - DCS0 2½ brass cap (properly mkd) cont next page

