

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; & 1 & 2, T31-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6754)

Set post cor. secs. 35, 36, 1 and 2, from which
An Oak 10" dia., bears N.85°W., 47 lks.
An Oak 10" dia., bears S.12°W., 67 lks.
An Oak 15" dia., bears N.77°E., 39 lks.
An Oak 15" dia., bears S.25°E., 64 lks.

Douglas Co. Surveyors Office - John M. Powell and crew - Aug. 1966 - C.S. File 54/28-83

Found - 10" Oak now stob, N.85°W., 31.0 ft., shows good scar
10" Oak now 15" S.12°W., 44.2 ft., shows good scar.
15" Oak now stob S.25°E., 42.2 ft., scribe visible "2W".
15" Oak now 26" N.77°E., 25.1 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office
T30S R S35|S36
T31S 2 S 2|S 1
W 1966

New BTs- 17" W.Oak N.30°W., 39.3 ft. mkd. T30S R2W S35 CSBT
15" W.Oak S.22°E., 45.4 ft. mkd. T31S R2W S1 CS BT.

Les Fanning - 2/2001 - C.S. File 65/36-9

Found - 1" galv. iron pipe exposed 20" above ground with a 2½" dia., brass cap firmly affixed to the top stamped as per rec.

From which OBTs:

Was 10" now fallen & rotted Oak, root crown bear N.81°W., (Rec. N.85°W.) 31.0 ft. (Rec. 47 lks)
Was 10" now 21" Oak bears S.10°30'W., (Rec. S12°W.) 44.2 ft. (Rec. 67 lks) with healed face.
Was 15" now 30" Oak bears N.81°E., (Rec. N.77°E.) 25.1 ft. (Rec. 39 lks.) with healed face.
Was 15" now rotted Oak root crown bears S.25°E., (Rec.), 42.2 ft. (Rec. 64 lks.)

BTs by Powell:

Was 17" now 20" Oak snag bears N.27°30'W., (Rec N.30°W.) 39.3 ft. (Rec.) with good scar.

Was 15" now 21" Oak bears S.24°E., (Rec. S.22°E.) 45.4 ft. (Rec.) with healed face. This tree is a second trunk from the same root crown as the Orig. missing in this section.

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; & 1 & 2, T31-2

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

New - 16" D.Fir bears N.29°W., 33.3 ft. which I scribed "T30S R2W S35 BT" on double face. I placed a brass washer stamped "PLS 1941" in the lower face.
 All BTs were painted with a red 6" band & faces. F.S. sign 54-9 attached to the back of each tree. BT tags were updated or replaced.
 Magnetic decl. 17°30'E (Determined from record of posted line to north)

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hillman - 6/18/2015 - C.S. File 65/90-71

Found - 2½" brass cap on 1¼" galvanized iron pipe, projecting 20" above the ground. Build mound of stone 2' base x 8" tall, cap now projects 12" above a mound of stone.
 A root hole & rotten remains of oak bears, N.84°W., 30.6 ft. with no marks. (N.85°W., 31.0') 1857 (N.81°W., 31.0') 2001
 A root hole bears. S.11°30'W., 45.3 ft, oak log with a healed double blaze. (S.12°W., 44.2') 1857, (S.10°30'W., 44.2') 2001
 A 30" oak bears N.79°15'E., 27.8 ft, with a healed single blaze that does not face corner. Oak leans heavy south. (N.77°E., 25.7') 1857, (N.81°E., 25.1') 2001
 A 22" oak root crown bears S.25°30'E., 43.1 ft, with new live stem growing from back of root crown, now shows burl where face should be. (S.25°E., 42.2') 1857 (S.25°E., 42.2') 2001
 A 16" Oak snag bears N.27°45'W., 39.8 ft, with a healed single blaze. (N.30°W., 39.3') 1966 (N.27°30'W., 39.3') 2001
 A 20" Oak bears S.24°30'E., 45.4 ft, with a healed double blaze. (S.22°E., 45.4') 1966 (S.24°E., 45.4') 2001
 A 19" fir bears, N.32°30'W., 33.6 ft. With a healed double blaze. (N.29°W., 33.3') 2001

New - A 11" FIR BEARS S.34°15'W., 22.9 ft marked "T31SR2WS2" "BT" on a double blaze.

Method of measurement - Leica TCRA 1103+ total station hold N.89°38'26"W. on steel post found 59.3 ft west from corner. Bearings to center. Distances to nail set side center.

Note - Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; & 1 & 2, T31-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Lat: N 42°54'59.611" Long: W 122°54'10.768"
Ellipsoid Height: 2590 ft.
Datum: WGS84
Source: Cell phone GPS, for navigation to corner.