

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6755)

Set ¼ sec. post and built stone mound, from which
A Fir 24" dia., bears N.14°W., 18 lks.
A Fir 24" dia., bears N.26°E., 17 lks.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct. 1968 - C.S. File 54/73-11

Found - 24" D.Fir, now stump, N.26°E., 11.2 ft.
24" D.Fir, now down, N.14°W., 11.9 ft., tree badly splintered and torn apart to find scribe "BT".
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 35 | S 36
1968
New BTs- 11" R.Fir S.51°E., 13.0 ft. mkd. ¼ S36 CS BT.
10" R.Fir N.62°W., 15.2 ft. mkd. ¼ S35 CS BT.

Fd. BC & 4 BTs 1978 by G. Baughman - M65-56

Jonathan B. Drew, II, USFS - Assisted by: Andrew Hillman - 6/8/2015 - C.S. File 65/90-66

Found - A 2½" brass cap on 1¼" galvanized iron pipe, projecting 8" above the ground.
(24" Fir) 1857 (down fir) 1968. Not searched for.
(N.14°W., 11.9 ft) 1857
36" Fir stump with a healed single blaze. (N.26°E., 11.2 ft.) 1857
18" fir with a healed double blaze. (S.51°E., 13.0 ft.) 1968
18" fir with a healed double blaze. (N.62°W., 15.2 ft.) 1968
Note - No new accessories added - No new measurement taken
Clear brush from around monument and to BTs. Tie flagging to monument and guard posts, paint BT faces & a 6" band at head height, add new nails to existing BT tags & add new tags where needed.
Lat: N 42°55'25.868" Long: W 122°54'10.607"
Ellipsoid Height: 2625 ft.
Datum: WGS84
Source: USGS Quad map. For navigation to corner.