

PRIMARY CORNER DESCRIPTION Sec Cor for 13, 14, 23 and 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6757)

Set post cor. secs. 13, 14, 23 and 24, from which
An Oak 36" dia., bears S.3°E., 85 lks.
An Oak 36" dia., bears S.58°W., 184 lks.
An Oak 24" dia., bears N.12°E., 140 lks.
An Oak 15" dia., bears N.22°W., 204 lks.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson;
Loren Weber - Aug. 2, 1940 - C.S. File 16/55

Location identified from one original BT which is down but scribe marks legible and two other which check for bearing and distance but marks obliterated.
Set Cedar post in field for corner, from which
Oak 16" dia., bears N.55½°W., 100.0 ft. mkd. T20S R2W S14 CS BT.
Oak 14" dia., bears N.2°E., 46.6 ft. mkd. T30S R2W S13 CS BT.
Fir 24" dia., bears S.74°W., 118.4 ft. mkd. T30S R2W S23 CS BT.
No tree near in SE.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam - July 3, 1959 - C.S. File 49/86-3

Found all 3 BTs as recorded by B.B.I., in 1940. Distances to BTs are OK. I find bearings thus:
16" Oak, Rec. N.55½°W., I find to be N.51°W.
14" Oak, Rec. N.2°E., I find to be N.4°E.
24" Fir, Rec. S.74°W., I find to be S.76°W.
Corner in field. I do not set brass cap. I do mark bearing object:
Chisled 2" x 2" + on top of 2 ft. x 4 ft. x 1 ft. sandstone which is also in field, bears S.69½°E., 46.6 ft.

BLM resurvey by C. Albert White, Cadastral Surveyor, under Group #524, surveyed Aug/Sept. 1963 - (DCSO records Vol. 32 Page(s) 13408)

The sec. corner, determined from an original bearing tree and subsequent trees marked by the County:
An Oak 35" dia., bears N.26½°E., 138 lks. dist., mkd. by Hathorn in 1857, with a double blaze, rotted out, and opened in 1940. (Rec. brg. & dist., N.22°E., 140 lks.)
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 13, 14, 23 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and trees mkd. by Irving in 1940:
 An Oak 15" dia., bears N.4°E., 71 lks. dist., mkd. R2W S,
 on partially healed blaze.
 A Fir 28" dia., bears S.75½°W., 181 lks. dist., mkd. with
 a healed blaze.
 An Oak 17" dia., bears N.52°W., 151 lks. dist., mkd. S R2W
 S14 C BT, on healed bark blaze in cambium layer.
 and a bearing object mkd. by Byron in 1959:
 A sandstone boulder, 4 x 2 x 1 ft., above ground, firmly
 in place, bears S.69½°E., 71 lks. dist., mkd. with a
 chiseled cross (X) on top.
 At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
 and in a mound of stone, 2 ft. base, to top, with brass cap
 mkd:

T	30	S	R	2	W
	S	14	S	13	
	S	23	S	24	
					1963

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
 Stephen J. Flause - 10/23/2000 - C.S. File 66/16-55

 Found - 1963 BLM BC/IP protrudes 4" out of ground.
 16" now 20" dia., W.Oak with a fully healed double
 blaze bears N.52°W., 99.7 ft. 1940
 14" now 15" dia., W.Oak with a fully healed double
 blaze, bears N.4°E., 46.9 ft. 1940
 24" now 28" dia., 30 ft. high D.Fir snag with a
 fully healed single blaze, bears S.75½°W., 119.5
 ft. 1940
 2'x4'x1' high sandstone outcrop top center fits
 with record, S.69½°E., 46.6 ft., chiseled "+" now
 gone. 1959
 24" now 30" dia., 8 ft. high W.Oak snag showing
 evidence of being previously opened with two
 rotted blazes, bears N.13½°E., 90.2 ft. (Orig.
 rec. N.12°E., 92.4 ft.) OBT
 New - 15" dia., D.Fir double blazed & scribed "T30S R2W
 S23 CS BT" bears S.57°W., 100.0 ft.
 Corner lies in open field & 3-way fence corner,
 bears N.38°W., 59 ft. to fence corner.
 Mound of stone set around base of BC/IP along with
 a metal witness post.
 Note - Compass dec. 17½°E.

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72

Found - 3" brass cap in stone mound.
22" W.Oak, N.52°W., 99.7', healed double blaze.
18" W.Oak, N.4°E., 46.9', healed double blaze.
3' stump remnant, N.13°30'E., 90.2'
17" D.Fir S.57°W., 100.0', healed double blaze.