

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCS0 records Vol. 16 Page(s) 6758)

-----  
Set ¼ sec. post, from which  
A Sugar Pine 12" dia., bears N.10°W., 15 lks.  
A Laurel 12" dia., bears N.2°E., 31 lks.

-----  
Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-37

-----  
Found - 12" now 22" Laurel N.2°E., 20.5 ft., opened earlier but below face, opened high for "BT".  
No trace of NW. BT.

¼ corner point falls on rock face, unable to set corner at proper point.

Set WIT. COR. brass cap mkd: County Surveyors Office  
T 30 S R @ W  
Wit. Cor. 5' South to  
¼ S 14 | S 13  
1968

New BTs- 14" Cedar N.60°W., 18.6 ft. mkd. WC ¼ S14 CS BT.  
16" D.Fir S.43°E., 196 19.6\* ft mkd. WC ¼ S13 CS BT.

This corner lies just North of small rock outcrop.

\*corrected 11/15/2017 - DCS0 JC

-----  
Ron Quimby - Crew: N. Fromdahl & R Heichel - 11/2017 - C.S. File 65/99-32

-----  
Condition report only

Found - 2½" DCS0 brass cap (properly mkd)  
24" cedar N.60°W., 18.1 ft. Good scar.  
22" D.fir S.43°E., 19.6 ft.  
T post 2' north  
T post 3' west.  
Compass decl. 15½°E.

-----  
Brent Knapp - For: Roseburg Resources Co. - 2/2022 - M180-72

-----  
Found - 2.5" brass cap (5' witness corner)  
24" cedar, N.60°W., 18.1', good scar.  
22" D.Fir, S.43°E., 19.6'  
T post, 2' North  
T post, 3' West.