

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11 & 12 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6802-03)

Set a porphyry stone 12x8x6 ins., 8" in the ground for cor. of secs. 11 and 12, marked with 1 notch on E. edge, from which

A Madrone 18" dia., bears N.41½°E., 42 lks. dist. mkd. T30S R2W S12 BT.

A Madrone 10" dia., bears N.55°W., 13 lks. dist. mkd. T30S R2W S11 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: R.G. Boyd - Jan. 26, 1959 - C.S. File 42/421-4

Determined by O.B.T.s;

20" Laurel windfall bears N.41°E., 27.7 ft., found scribe. At corner point, found stone and SET 3/4" x 48" Iron pipe, from which

7" Fir bears S.4°W., 19.2 ft. mkd. S13 BT.

5" Fir bears S.80°W., 8.0 ft. mkd. S13 R2W BT.

12" Laurel bears N.52°W., 39.0 ft. mkd. S11 T30S R2W BT.

6" Fir bears N.5°W., 33.3 ft. mkd. S11 R2W BT.

NE. corner sec. 14 bears West, 120.0 ft.

Fd. OK, Nov. 1968, DCSO, J. Powell C.S. 54/73-38A

Jim Landrum, U.S. Forest Service (Deputized by the County) Wit: L. Herzstein - June 21, 1983 - C.S. File 62/10-12

Found - 1" Iron pipe, firmly set, projecting 22" above the ground, set by Markham in 1959.

Orig. corner stone 6" x 4" x 8" on top of ground, alongside iron pipe, with no marks visible. I used iron pipe as corner point, as it is the only solid point in the ground.

Orig. BT, a root hole, N.41°E., 27.7 ft. with 20" Madrone log alongside with decayed blaze.

1959 BT, a 12" D.Fir stump S.4°W., 19.2 ft. with healed blaze.

1959 BT, a 11" D.Fir stump S.80°W., 8.0 ft. with healed blaze.

1959 BT, a 14" Madrone snag N.52°W., 39.0 ft. with scribe marks "S11 R W" visible on previously opened blaze.

(Cont. Next Page)

