TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page 6835)

Set a conglomerate stone 14x10x4 ins., 9½" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 16" dia., bears N.60°E., 25 lks. mkd. ¼ S12 BT
A Fir 16" dia., bears N.31½°W., 38 lks. mkd. ¼ S11 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-39

Found - 16" D.Fir now stump, N.31½°W., 25.1 ft., scribe visible.
16" D.Fir now stump, N.60°W., 16.5 ft., opened for scribe.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 11|S 12
1968

New BTs- 16" D.Fir S.72°W., 60.9 ft. mkd. ¼ S11 CS BT.
14" D.Fir S.84°E., 29.8 ft. mkd. ¼ S12 CS BT.

Fd. OK, April 1995 by Nygren - M 121-76

Fd. & used on BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June/July 1998 - (DCSO recs. Vol. 53 Pg(s) 20348-9)

Found OK by B. Shaner, Mar. 2001 - M132-75 & CS65/36-12D

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2232, Surveyed Oct. 2008/April 2009 - (DCSO records Vol. 57 Page(s) 22663-4)

The ¼ sec. cor. of secs. 11 & 12, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above the top of a mound of stone 3½ ft. base, 1½ ft. high, with brass cap (properly) mkd.
from which the remains of the orig. bearing trees
A sawed, decayed fir stump, 18" dia., bears N.60°E., 16.5 ft., with no marks visible.
A sawed, decayed fir stump, 19" dia., bears N.31½°W., 25.1 ft., with scribe marks S11 BT visible on a partially healed, decayed blaze.
and BTs mkd. by the Douglas County Surveyor's Office, in 1968
A fir, 22" dia., bears S.85¾°E., 29.7 ft., with a healed blaze.

continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 25" dia., bears S.72¼°W., 61.1 ft., with a healed blaze.
Corner is located on a S. slope.