

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6836)

Set a conglomerate stone 15x10x4 ins., 10" in the ground for cor. of secs. 1, 2, 11 and 12, marked with 5 notches on S. and 1 notch on E. edge, from which
A Fir 8" dia., bears N.46½°E., 19 lks. dist. mkd. T30S R2W S1 BT.
A Fir 36" dia., bears S.50°E., 59 lks. dist. mkd. T30S R2W S12 BT.
A Fir 12" dia., bears S.59°W., 36 lks. dist. mkd. T30S R2W S11 BT.
A Madrone 6" dia., bears N.29°W., 44 lks. dist. mkd. T30S R2W S2 BT.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-40

Found - Stone, approx. size, no marks.
8" now 13" D.Fir N.46½°E., 12.5 ft., shows good scar
36" D.Fir, now stump S.50°E., 38.9 ft., shows good scar.
12" now 16" D.Fir S.59°W., 23.8 ft., shows good scar.
6" now 10" Laurel N.29°W., 29.0 ft., faint rotten scribing visible.

Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
S 2 | S 1
S 11 | S 12
1968

New BT - 9" Laurel S.32°E., 38.5 ft. mkd. T30S R2W S12 CS BT
Reblazed and rescribed:
10" Laurel N.29°W., 29.0 ft. mkd. T30S R2W S2 CS BT