

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6838-39)

Set a basalt stone 18x10x10 ins., 12" in the ground, for ¼ sec. cor., marked ¼ on W. face, from which
 A Madrone 10" dia., bears East, 19 lks. dist. mkd. ¼ S1 BT
 A Fir 7" dia., bears N.80°W., 15 lks. dist. mkd. ¼ S2 BT.

Survey by Robert M. Thompson - Jan. 12, 1956 - C.S. File 42/199

I find corner stone in position and Madrone BT in Sec. 1 standing but with face rotted out. No trace of the Fir BT in sec. 2.
 I scribe 2 new BTs as prescribed by law:
 18" D.Fir N.84½°W., 21.9 ft.
 40" Sugar Pine N.30°E., 47.6 ft.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 1968 - C.S. File 54/73-29

Found - Stone at ¼ corner, 8x10x10, "¼" on West face.
 18" D.Fir, now down, N.84½°W., 21.9 ft., scribe visible.
 40" now 40" Sugar Pine, N.30°E., 47.6 ft., pitched over, scribe visible.

Set Brass cap at cor. mkd: County Surveyors Office
 T 30 S R 2 W
 ¼ S 2 | S 1
 1968

New BT - 18" Fir N.53°W., 86.8 ft. mkd. ¼ S2 CS BT.
 Corner lies on top of large ridge, running NE.

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20340)

The ¼ sec. cor. of secs. 1 & 2, perpetuated by Thompson, in 1956, further perpetuated by Powell, in 1968, monumented with an iron pipe, 1¼" diam., firmly set, projecting 13" above ground, (alongside of which is the original basalt stone), with brass cap mkd. COUNTY SURVEYORS OFFICE
 T 30 S R 2 W
 1/4 S 2 | S 1
 1968

from which the remains of a bearing tree mkd. by Thompson
 continued next page

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed pine stump, 44" diam., bears N.30°E., 73½ lks., with scribe marks S1 visible on opened upper blaze and BT visible on lower blaze.
and the remains of a bearing tree mkd. by Powell
A sawed fir stump, 18" diam., bears N.53°W., 131½ lks., with scribe marks ¼ S2 CS BT visible on partially healed blaze.
and new bearing trees
A fir, 9" diam., bears S.28½°E., 33½ lks., mkd. ¼ S1 BT.
A fir, 12" diam., bears S.58½°W., 31 lks., mkd. ¼ S2 BT.
Corner is located on top of wide ridge, bears N.40°E., and S.50°W.