

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2 only (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6197) (Dup. pg 6821)

-----

Set a basalt stone 15x10x6 ins. 10" in the ground for cor. of secs. 1, 2, 35 and 36, marked with 1 notch on E. and 5 notches on W. edge, from which

A Cedar 12" dia., bears N.6 3/4°E., 63 lks. mkd. T29S R2W S36 BT.

A Fir 5" dia., bears S.11°E., 36 lks. mkd. T30S R2W S1 BT.

A Fir 5" dia., bears S.17½°W. 41 lks. mkd. T30S R2W S2 BT.

A Fir 14" dia. bears N.46°W. 22 lks. mkd. T29S R2W S35 BT.

---

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6214-15)

-----

Intersect the cor. of secs. 1, 2, 35 and 36, which is a stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 1 and 2, T30S R2W only by destroying all marks referring to secs. 35 and 36. From cor.

A Fir 5" dia., bears S.11°E., 36 lks. dist. mkd. T30S R2W S1 BT. (Old BT)

A Fir 15" dia., bears S.43°W., 85 lks. dist. mkd. T30S R2W S2 BT. (New BT)

---

Douglas Co. Surveyors Office - John M. Powell, Jack Heritage; W. Penley - Nov. 1968 - C.S. File 54/73-27

-----

Found - Stone at corner approx. size and 5 grooves on West side.

5" W.Fir, now dead, S.11°E., 23.8 ft., scribe vis.

15" D.Fir, now down, S.43°W., 56.1 ft., shows scar.

Set Brass cap at cor. mkd: County Surveyors Office

T	29	S		S36
T	30	S	R2W ¼	
				<u>S 2   S 1</u>

1968

New BTs- 7" W.Fir S.12°W., 34.4 ft. "T30S R2W S1 CS BT"

9" W.Fir S.4°E., 43.0 ft. mkd. "T30S R2W S1 CS BT"

15" D.Fir N.47°W., 14.7 ft. "T29S R2W S36 CS BT"

---

Fd. & used on BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June/July 1998 - (DCSO recs. Vol. 53 Pg(s) 20331-2)