

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 13 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6758)

Set ¼ sec. post, from which
A Fir 10" dia., bears N.30°W., 4 lks.
A Fir 12" dia., bears S.70°W., 16 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6797 and 6802)

(Page 6797)
The ¼ sec. cor. practically obliterated, bears South 15 lks. dist. No trace is found of the post and the bearing trees are deeply overgrown.
(Page 6802)
I re-establish the old ¼ sec. cor. in its original position as the ¼ sec. cor. on N. bdy. sec. 13, only, as follows:
Set a porphyry stone 12x9x8 ins., 8" in the ground for ¼ sec. cor. on N. bdy. sec. 13, marked ¼ on S. face, from which
A Fir 18" dia., bears S.77°E., 51 lks. dist. mkd. ¼ S13 BT.
A Fir 18" dia., bears S.70°W., 17 lks. dist. mkd. ¼ S13 BT.
Obliterate marks on former bearing tree referring to sec. 12.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Wit: O.A. Keatley - March 24, 1960 - C.S. File 42/421-14

Determined by O.B.T.:
33" Fir S.77°E., 33.6 ft., found scribe.
At corner point, found stone and SET 1/2" x 30" Iron pipe, from which
14" Cedar N.17°W., 27.8 ft. mkd. ¼ S13 BT.
10" Fir S.4°W., 52.0 ft. mkd. ¼ S13 R2W BT.
So. 1/4 Corner S.12 bears East 58.0 ft. distance.

Dennis Gaylord, U.S.Forest Service (Deputized by the County) Wit: James Davis - Aug. 30, 1978 - C.S. File 60/11-34

Found - 1" x 30" Iron pipe set firmly alongside a 6" x 8" x 12" stone.
Orig. BT, a 23" D.Fir stump bears S.77°E., 33.6 ft. scribing visible on previously opened blaze, "S13 BT".
A 17" Cedar bears N.17°W., 27.4 ft. scribing visible on a partially healed blaze, "BT ¼ S" on a single blaze.
(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 639500

PRIMARY CORNER DESCRIPTION North 1/4 Cor. Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 12" Fir stump bears S.2°W., 51.2 ft. scribing visible, "B".
I reference the iron pipe and moving it aside, I replace it with a 1½" iron pipe with a 2½" brass cap attached and stamped: "County Surveyors Office T30S R2W ¼ S13 1978". I bury the stone and 1" pipe alongside the brass cap.
New BT - A 6" D.Fir bears S.33°30'E., 46.0 ft. scribed "¼ S13 CS BT" on a double blaze.
I placed County BT signs on all BTs and BT stumps.
Local attraction created by a steel fence post setting 1.2 ft. East of corner.

Fd. & used on BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20346)

Bruce Shaner - March. 2001 - M132-75 & C.S. File 65/36-12E

Found all as recorded by USBLM, Wayne Rogers, **EXCEPT:**
A 14" D.Fir BT marked by Dennis Gaylord bears S.33½°E., (USBLM rec. S.61¼°W.) a distance of 45.5 ft. (County tag shows S.33½°E., 45.0 ft.)
Corner is 300 ft. from old logging road spur.

2