

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 & 36

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6755)

Set ¼ sec. post, from which
A Laurel 6" dia., bears N.40°E., 6 lks.
A Fir 6" dia., bears S.30°E., 12 lks.

Survey by Glenn Baughman, OLS #536 - For: U.S. Forest Service
May 1978 - M 70-15

Set 2" x 30" I.P. with brass cap mkd. "T30S R2W WM ¼ S25 S36
1978 OLS 536", from which
8" D.Fir bears S.70°W., 9.0 ft. scribed ¼ S36 BT.
8" D.Fir bears N.29°W., 5.8 ft. scribed ¼ S25 BT.

Troy Rambo - For: Seneca Jones Timber Co. & Roseburg
Resources Co. - 6/2010 - M160-77

Found - Brass cap per M70-15
9" DF with a healed face, bears S.70°W., 9.0 ft.
12" DF with a healed face, bears N.29°W., 5.8 ft.
A fence post with a USFS sign, bears N.71°W. 4.8 ft.
New - Scribed "¼ S36 BT" on a 10" DF, bears S.31°E., 25.0
ft.