

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6756)

Set ¼ sec. post, from which
A Laurel 12" dia., bears N.4°W., 25 lks.
A Fir 39" dia., bears S.52°E., 64 lks.

Douglas County Surveyors Office - Gary L. Langlitz, Deputy - P. Earle, crew - Dec. 9, 1974 - C.S. File 57/12-7

This corner set from survey of the South line of sec. 24, its location determined by single proportionate measurement. An exhaustive search of the area yielded no trace of the original corner.

At the corner point, WE SET a 1" x 30" I.P. with brass cap attached mkd: County Surveyors Office
T 30 S R 2 W
¼ S 24
 S 25
 1974

from which
A 20" D.Fir bears N.51°E., 51.7 ft. scribed "¼ S24 CS BT".
The blazes on this BT face South.
A 10" Madrone bears S.3°W., 24.0 ft. scribed "¼ S25 CS BT".

Survey by Loyd R. Moffit, LS #944 - For: U.S. Forest Service April 1985 - C.S. File 63/8-4

Found - A 2" brass cap on a 1" Iron pipe.
An 18" Fir bears N.51°E., 51.7 ft., scar visible.
A down 12" Madrone is destroyed.
New BT - A 10" Madrone which bears S.55°E., 18.0 ft. mkd. ¼ S25 BT.