TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6757)

Set ¼ sec. post, from which
An Alder 6" dia., bears N.73°E., 27 lks.
An Alder 10" dia., bears S.50°W., 31 lks.

Ben B. Irving, Deputy County Surveyor - Wit: N.E. Richardson; Loren Weber - Aug. 2, 1940 - C.S. File 16/55

Original corner obliterated.
Set a rock 6" x 9" x 20" mkd. X ¼ for corner with Cedar post 6" x 6" x 48" alongside, midway between corner 13, 24, T30S R2W.; 18 & 19, T30S R1W, - 13, 14, 23 and 24, T30S R2W., from which
A Fir 20" dia., bears N.40°W., 6.7 ft. mkd. ¼ S13 CS BT.
A Fir 36" dia., bears S.10°E., 41.0 ft. mkd. ¼ S24 CS BT

Douglas Co. Surveyors Office - John M. Powell, J. Heritage & W. Penley, crew - Nov. 14, 1968 - C.S. File 54/73-36

Found - Stone 6x9x20" at ¼ corner. Also post mkd. "¼".
20" now 28" D.Fir N.40°W., 6.7 ft., bark scribed.
36" now 40" D.Fir S.10°E., 41.0 ft., bark scribed.
Set Brass cap at cor. mkd: County Surveyors Office
T 30 S R 2 W
¼ S 13 / S 24
Reblazed and rescribed: 1968
28" D.Fir N.40°W., 6.7 ft. mkd. ¼ S13 CS BT.
40" D.Fir S.10°E., 41.0 ft. mkd. ¼ S24 CS BT.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 10/23/2000 - C.S. File 66/16-54

Found - 1968 DCSO BC/IP protrudes 12" above a mound of stone (marks on stone not looked at)
20" now 38" dia., D.Fir with a fully healed double blaze & bark scribing "¼ CS" bears N.29°W., 7.9 ft. (Rec. N.40°W., 6.7 ft.) 1940
36" now 52" dia., D.Fir with a fully healed single blaze & bark scribing "¼ S" bears S.7°E., 41.0 ft. (Rec. S.10°E., 41.0 ft.) 1940
New - 7" dia., Maple double blazed & scribed "¼ S24 CS BT" bears S.73°W., 9.8 ft.
9" dia., Hemlock double blazed & scribed "¼ S13 CS BT" bears N.27°E., 25.0 ft.
Note - Compass Dec. 17½°E