

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 640540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Gerald Nygren, for John Hayden - April 1995 -  
M 121-76.

-----  
Set 5/8" x 30" iron rod with yellow plastic cap marked  
"Nygren LS1035", from which  
Bearing trees scribed -  
10" D.Fir, S.40°E., 47.7 ft.  
7" D.Fir, N.37°E., 25.1 ft.  
8" D.Fir, N.73°W., 19.6 ft.  
8" D.Fir, S.76°W., 18.6 ft.

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor  
and Robert Browning, under Group #1883 surveyed June & July  
1998 - (DCSO recs. Vol. 53 Pg(s) 20347)

-----  
The center ¼ sec. cor. of sec. 12, established by Nygren, in  
1995, and is accepted as the corner, monumented with an iron  
rod, 5/8" diam., firmly set, flush with the ground, with  
yellow plastic cap mkd. NYGREN LS 1035, from which bearing  
trees mkd. by Nygren:

- A fir, 10" diam., bears N.36½°E., 38 lks., with  
fragmentary scribe marks visible on partially healed  
blaze.
- A fir, 15" diam., bears S.40°E., 69½ lks., with  
fragmentary scribe marks visible on partially healed  
blaze.
- A fir, 11" diam., bears S.77°W., 28 lks., with a healed  
double blaze.
- A fir, 11" diam., bears N.70°W., 29 lks., with a healed  
double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., directly  
over the iron rod, 28" in the ground, with brass cap mkd.

T 30 S R 2 W

C 1/4 S 12

1998

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

Found OK by B. Shaner, Mar. 2001 - M132-75 & CS65/36-12G