

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 640640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20342)

Point for the center ¼ sec. cor. of sec. 1, at intersection with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, in a collar of stone, with brass cap mkd.

T 30 S R 2 W
C 1/4 S 1
1998

from which

A fir, 8" diam., bears N.72½°E., 4½ lks., mkd. C¼S1 BT.

A fir, 11" diam., bears S.29½°W., 49 lks., mkd. C¼ S1 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Corner is located in an abandoned dirt road, 20 lks. wide, bears N.30°W., and S.30°E.

From this point, the BLM Geodetic Control Station No. EC 41276, at latitude 42°59'44.769"N. long. 122°53'34.386"W., (NAD 1983), determined by the NAVSTAR Global Positioning System, bears S.8°13'27"W., 7.331 chs., monumented with an aluminum cap, 3¼" diam., firmly set, flush with the ground, mkd. EC 41276 GPS 1998.