

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 1 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 15 Page(s) 6196) (Dup. pg. 6820)

-----

Set a basalt stone 14x8x5 ins., 9½" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Fir 7" dia., bears N.67°W., 29 lks. dist. mkd. ¼ S36 BT

A Fir 8" dia., bears S.20°E., 46 lks. dist. mkd. ¼ S1 BT.

GLO resurvey by Elmer F. Strickler, U.S. Transitman, under Special Instructions dated Jan. 22, 1917 - (DCSO records Vol. 15 Page(s) 6214)

-----

Intersect the ¼ sec. cor., which is a basalt stone, firmly set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 1, T30S R2W only, by destroying all marks referring to sec. 36 and mark ¼ on S. face, from cor.

A Fir 6" dia., bears S.7°45'W., 53 lks. dist. mkd. ¼ S1 BT. (New BT)

A Fir 8" dia., bears S.20°E., 46 lks. dist., mkd. ¼ S1 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Oct/Nov. 1968 - C.S. File 54/73-30

-----

Found - Stone at ¼ cor. about size, no marks visible.  
8" D.Fir now stump, S.20°E., 30.4 ft. opened for scribe.

No trace of SW. bearing tree.

Set Brass cap at cor. mkd: County Surveyors Office

|        |     |   |       |
|--------|-----|---|-------|
| T 29 S | R2W | ¼ | _____ |
| T 30 S |     |   | S 1   |

1968

New BTs- 10" W.Fir S.21°E., 23.7 ft. mkd. ¼ S1 CS BT.  
9" W.Fir S.24°W., 28.3 ft. mkd. ¼ S1 CS BT.

This corner lies 25.7 ft. East of ¼ cor. sec. 36, T29-2

Fd. OK, July 1973 by W. Haines (See BLM office for admin survey)

continued next page

1

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 640700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 1 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20329-30

-----

Beginning at the ¼ sec. cor. of sec. 1 only, on the N. bdy. of the Tp, perpetuated by Powell, in 1968, monumented with an iron post, 1¼" diam., firmly set, projecting 2" above ground, (alongside of which is the original basalt stone), with brass cap mkd.  
COUNTY SURVEYORS OFFICE

T 29 S R 2 W

1/4 S 1

T 30 S

1968

from which the remains of an original bearing tree

A sawed fir stump, 25" diam., bears S.20°E., 46 lks., with an opened blaze, no scribe marks visible.

and the remains of a bearing tree mkd. by Strickler, in 1909

A decayed fir stump, size indeterminate, bears S.7°W., 64 lks., no marks visible. (Record S.7°45'W., 53 lks.)

and bearing trees mkd. by Powell

A fir, 15" diam., bears S.22½°E., 36½ lks., with a healed blaze.

A fir, 12" diam., bears S.23½°W., 42½ lks., with a healed blaze.

and a bearing tree of no record

A pine, 14" diam., bears N.58½°E., 4½ lks., with a healed blaze.