

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 700240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 25; & S. 30, T30-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6650)

Marked a Fir 6" dia. for 1/4 sec. corner, from which
A Fir 12" dia., bears S.40°W., 5 lks.
A Maple 12" dia., bears N.12°E., 16 lks.

Survey by Glenn Baughman - For: U.S. Forest Service (Umpqua National Forest) - July 1968 - C.S. File 55/83-6 and M 36-12

No evidence found of 1857 survey by Hathorn.

Set 2" x 30" I.P. with brass cap mkd: R T 30 S R
 2 1/4 S 25 | S 30 1
 W 1968 W
 OLS 536

New BTs- 48" dia. Cedar bears N.12°E., 22.5 ft. mkd. T30S R1W
 S30 BT.
 12" dia. Fir bears S.38°W., 39.4 ft. mkd. T30S R2W
 S25 BT.

Placed USFS BT signs on both trees, breast high and facing pipe.

Survey by Glenn Baughman, LS #536 - For: U.S. Forest Service
May 1978 - M 70-15

Found - 1968 brass cap set by Baughman and Ackaret.
 48" Cedar stump bears N.12°E., 22.5 ft.
 No BT in SW quadrant.

New BTs- 8" D.Fir bears S.9°W., 34.2 ft. scribed 1/4 S25 BT.
 9" D.Fir bears N.51°E., 51.0 ft. scribed 1/4 S30 BT.

Gerald Nygren - For: Seneca Jones Timber Co. - Feb. 2015 -
M169-12

Found - 1968 Brass cap per M36-12
 48" Cedar stump bears N.12°E., 22.5'
 16" D.Fir bears S.9°W., 34.2'
 9" D.fir bears N.51°E., 51.0' (dead)

New BTs- 11" D.Fir bears S.89°W., 15.2', scribed "1/4 S25 BT"
 12" D.Fir bears N.13°E., 18.7' scribed "1/4 S30 BT"