

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T30-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6651)

-----  
Set ¼ sec. post, from which  
A Fir 36" dia., bears N.10°E., 8 lks.  
A Fir 15" dia., bears N.15°W., 34 lks.

-----  
Glenn S. Baughman - For: U.S. Forest Service - July 1968 -  
C.S. File 55/83-1 and M 36-12

-----  
No evidence found of 1857 Hathorn corner.  
Set 2" x 30" I.P. with brass cap stamped: R T 30 S R  
2 ¼ S 24 | S 19 1  
W 1968 W  
OLS 536  
New BTs- 16" Fir bears N.57°E., 19.4 ft. mkd. ¼ S19 T30S R1W  
20" Fir bears West 3.5 ft. mkd. ¼ S24 T30S R2W  
Placed USFS BT signs on both trees, breast high and facing pipe.