

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; and 18, T30-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6651)

-----  
Set ¼ sec. post, from which  
A Fir 48" dia., bears S.10°W., 8 lks.  
A Fir 30" dia., bears S.50°E., 12 lks.

Grant and Art Evans - Nov. 1951 - C.S. File 41/66

-----  
Set Fir stake from 2 original BTs:  
48" Fir S.10°W., 8 lks., scribe marks plain.  
30" Fir now 42" S.50°E., 12 lks., scribe marks plain.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - June 1968 - C.S. File 54/59-91

-----  
Found - 38" D.Fir S.10°E., (Rec. S.10°W.) 5.3 ft., faint bark scribe "¼". Tree opened before, "BT" visible.

48" D.Fir now stump S.50°W., (Rec. S.50°E.) 7.9 ft.  
Find no other trees in area close to matching. Calls on South Umpqua fit good. Renew by using reverse bearing and original distance.

Set Brass cap at cor. mkd: County Surveyors Office  
R T 30 S R  
2W ¼ S13 | S18 1W  
1968

Reblazed and rescribed:  
38" D.Fir S.10°E., 5.3 ft. mkd. ¼ S18 CS BT.  
New BT - 12" R.Fir N.30°W., 10.8 ft. mkd. ¼ S13 CS BT.