

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T30-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6651)

-----  
Set post corner secs. 7, 18, 12 and 13, from which  
A Fir 15" dia., bears S.48°W., 35 lks.  
A Fir 6" dia., bears N.30°W., 30 lks.  
A Hemlock 6" dia., bears S.20°E., 14 lks.  
A Sugar Pine 6" dia., bears N.75°E., 10 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6701-02)

-----  
I re-establish the corner in its original position as follows: Set a porphyry stone 18x10x5 ins., 12" in the ground for corner of secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edge, from which  
A Sugar Pine 15" dia., bears N.18°E., 39 lks. dist. mkd. T30S R1W S7 BT.  
A Fir 8" dia., bears S.88°E., 39 lks. dist. mkd. T30S R1W S18 BT.  
A Fir 20" dia., bears S.48°W., 36 lks. dist. mkd. T30S R2W S13 BT.  
A Fir 15" dia., bears N.30°W., 31 lks. dist. mkd. T30S R2W S12 BT.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Dec. 1958 - C.S. File 42/421-2

-----  
Determined by O.B.T.s:  
24" Pine bears N.18°E., 25.7 ft., found scribe.  
14" Fir bears N.34°W., 20.4 ft.  
24" Fir bears S.47°W., 24.8 ft.  
At corner point, found Stone. Set 3/4" x 30" Iron pipe, from which  
5" Chinquapin bears N.87°W., 17.0 ft. mkd. S12 X BT.  
5" Chinquapin bears N.69°W., 25.8 ft. mkd. S12 T30S BT.  
Road bears West 230.0 ft. distance.

Douglas Co. Surveyors Office - Clell Goodwin; Gary Langlitz; Vic Cangie; Lenora Ladig, crew - Dec. 18, 1975 - C.S. File 57/39-42

-----  
Found - A stone, firmly set, 18"x10"x25", mkd. with 4 notches on the South side and at least 1 notch on the North.

(Cont. Next Page)

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T30-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Markham's 1958 3/4" x 24" I.Pipe is set alongside the stone, from which original BTs are located. Orig. 15" now 22" D.Fir, alive and well healed, bears S.44°W., 23.8 ft. (Rec. S.48°W., 23.8 ft.) Orig. 6" now 17" D.Fir, alive and well healed, bears N.34°W., 20.5 ft. (Rec. N.30°W., 20.5 ft.) 15" now 35" Sugar Pine mkd. during a subsequent government resurvey, alive and in good condition, bears N.18°E., 25.7 ft. A 5" now 7" Chnquapin (1958 Markham BT), alive, scribing visible on rotting face, bears S.88°W., 17.0 ft. (Rec. N.87°W., 17.0 ft.) A 5" now 6" Chinquapin (1958 Markham BT) in poor condition, scribe visible, bears N.72°W., 25.8 ft. (Rec. N.69°W., 25.8 ft.) At the corner point, WE SET a 1" x 30" I.Pipe, 26" in the ground, with brass cap attached, mkd: Douglas Co. Surveyor

	T 30 S		
R	S 12	S 7	R
2	S 13	S 18	1
W	1975		W

We place the corner stone on the East and Markham's pipe on the West side of the brass cap and mark the following BT:  
A 5" D.Fir scribed "NW S18 CS BT" on a double blaze, bears S.68°E., 32.3 ft.

Fd. OK, Dec. 1994 - M 121-45  
Fd. OK, April 1995 by Nygren - M 121-76  
Fd. 1975 DCS BC 7/2017 by D. Edwards - M174-30B