

TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only (E. bdy)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6703)

Set a conglomerate stone 12x12x10 ins., 8" in the ground for corner of secs. 1 and 12, marked with 1 notch on N. and 5 notches on S. edge, from which

A Fir 18" dia., bears S.24°W., 30 lks. dist. mkd. T30S R2W S12 BT.

A Fir 10" dia., bears N.55°W., 38 lks. dist. mkd. T30S R2W S1 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Jan/Feb. 1968 - C.S. File 54/59-36

Found - Stone at section corner.
15" now 25" D.Fir S.24°W., 19.8 ft, shows good scar.
16" now 22" double D.Fir, N.55°W., 25.1 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 30	S	R
2	S 1	S 7	1
W	S 12		W
	1968		

Old bearing trees OK, tagged same.
This corner lies 50.8 ft. South of sec. cor. for 6 & 7, T30-1

Fd. & used on BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June/July 1998 - (DCSO recs. Vol. 53 Pg(s) 20334-5)