

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6704)

Set a basalt stone 12x10x8 ins., 8" in the ground for ¼ sec. cor. on E. bdy. sec. 1, marked ¼ on W. face, from which
 A W.Oak 14" dia., bears S.70°W., 6 lks. dist. mkd. ¼ S1 BT
 A W.Oak 4" dia., bears N.81°W., 57 lks. dist. mkd. ¼ S1 BT

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Jan/Feb. 1968 - C.S. File 54/59-35

Found - 14" W.Oak S.70°W., 4.0 ft., found old axe work.
 No trace of NW. BT.
 12x10x8 basalt stone, firmly in ground "¼" on W. face.

Set Brass cap at cor. mkd: County Surveyors Office

	R	T 30 S	R
	2	S 1 ¼	1
	W	1968	W

New BTs- 5" D.Fir N.71½°W., 9.6 ft. mkd. ¼ S1 CS BT.
 10" W.Oak S.46½°W., 20.0 ft. mkd. ¼ S1 CS BT.
 This corner lies 81.2 ft. South of ¼ cor. sec. 6 only, T30-1

BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 2036-7)

The ¼ sec. cor. of sec. 1 only, perpetuated by Powell, in 1968, monumented with an iron pipe, 1¼" diam., firmly set, projecting 10" above ground (alongside of which is the original basalt stone), with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 30 S	
		R 1 W
¼	S 1	
	R 2 W	
	1968	

from which the remains of an original bearing tree
 An oak snag, 16" diam., bears S.70°W., 6 lks., with axe marks visible on decayed blazes.
 and the remains of bearing trees mkd. by Powell
 An oak snag, 10" diam. bears S.47°W. 30 lks. w/fragmentary scribe marks visible on partially healed double blaze.
 A fir, 12" diam., bears N.73¼°W., 14 lks., with a healed double blaze.
 and a new bearing tree
 A fir, 8" diam., bears S.57¼°W., 13½ lks., mkd. ¼ S1 BT.