TOWNSHIP 30 RANGE 02 POINT IDENTIFIER # 700641

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T30-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6652)

Set ¼ sec. post, from which
An Oak 10" dia., bears S.2½°E., 106 lks.
An Oak 10" dia., bears S.2°W., 125 lks.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #782, dated Dec. 1, 1908 - (DCSO records Vol. 16 Page(s) 6704)

I re-establish the old ¼ sec. corner in its original position as the ¼ sec. cor. on W. bdy. sec. 6, T30S R1W only, as follows:
Set a basalt stone 18x10x6 ins., 12" in the ground mkd. ¼ on E. face, from which
A Yellow Pine 28" dia., bears N.71°E., 88 lks. dist. mkd. ¼ S6 BT.
A W.Oak 12" dia., bears S.2½°E., 107 lks. dist. mkd. ¼ S6 BT.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones & W. Penley, crew - Jan. 1968 - C.S. File 54/59-34

Found - 18x10x6 basalt stone, firmly in ground "¼" on E. face.
28" Pine, now down, burnt, N.71°E., 58.1 ft.
No trace of SE. BT.
Set Brass cap at cor. mkd: County Surveyors Office

R	T 30 S	R
2	¼ | S 6	1
W	1968	W

New BTs- 9" Pine N.85°E., 12.0 ft. mkd. ¼ S6 CS BT.
5" Pine S.52°E., 3.5 ft. mkd. ¼ S6 CS BT.
This corner lies 81.2 ft. North of ¼ sec. 1, T30-2, and lies 5 ft. South of fence corner, running N. and E.

Fd. OK, Sept. 1993 by H. Pieske - M 117-62

Fd. & used on BLM dependent resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, under Group #1883 surveyed June & July 1998 - (DCSO recs. Vol. 53 Pg(s) 20337)