

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100297

PRIMARY CORNER DESCRIPTION Cor. Secs. 24 & 25, East, only; T30-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11045)

Set an iron post, 3 ft. long, 2" dia., 26" in the ground for cor. of secs. 24 & 25 only, with brass cap mkd:

T30S		T30S
S 24		R3E
S 25		S 30
R 2 E		
1928		

from which

A fir, 42" dia., bears S.7°W., 50 lks., mkd: T30S R2E S25 BT.

A cedar, 26" dia., bears N.13°W., 20 lks., mkd: T30S R2E S24 BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11140), established for secs. 19, 24, 25 & 30, on line (S.0°13'W., 5.69 chs). We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012