

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION CC Secs. 19 & 30, only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,
under Special Instructions dated Dec. 27, 1920 & Sept. 9,
1927 - (DCSO records Vol. 26 Page(s) 11045-6)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for
closing cor. of secs. 19 & 30, with brass cap mkd

	T30S	
T30S		T30S
	S 19	
R 2E		CC
	S 30	
S 24		R 3 E

1928

from which

- A fir, 40" dia., bears N.56°E., 51 lks., mkd: CC T30S R3E
S19 BT.
- A fir, 34" dia., bears S.71°E., 75 lks., mkd: CC T30S R3E
S30 BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11140),
established for secs. 19, 24, 25 & 30, on line (S.0°13'W.,
9.46 chs). We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by
Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012