

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100397

PRIMARY CORNER DESCRIPTION East Cor. Secs. 13 & 24, only; T30-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer,
under Special Instructions dated Dec. 27, 1920 & Sept. 9,
1927 - (DCSO records Vol. 26 Page(s) 11047-8)

Set an iron post, 3 ft. long, 2" dia., 32" in the ground, for
cor. of secs. 13 & 24, with brass cap mkd

_____	T30S	T30S
	S 13	R3E
	S 24	S 19
	R 2 E	1928

from which

A fir, 43" dia., bears S.19½°W., 79 lks., mkd: T30S R2E
S24 BT.

A fir, 34" dia., bears N.66°W., 96 lks., mkd: T30S R2E S13
BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11141),
established for secs. 13, 18, 19, & 24, on line (S.0°13'W.,
5.7 chs and West 24 lks.). We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by
Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012