

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION CC Secs. 18 & 19, only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11048)

-----

Set an iron post, 3 ft. long, 2" dia., 18" in the ground, to bedrock with a mound of stone around the post, for CC of secs. 18 & 19, with brass cap mkd:

T30S	T30S	
R 2E	S 18	CC
S 13	S 19	
	R 3 E	

1928

from which

A fir, 26" dia., bears N.11°E., 55 lks., mkd: CC T30S R3E S18 BT.

A larch, 34" dia., bears S.19½°E., 183 lks., mkd: CC T30S R3E S19 BT.

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11141), established for secs. 13, 18, 19, & 24, on line (S.0°13'W., 9.71 chs. and West 24 lks.) We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012