

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100436

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 13 only; T30-2E

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11048-9)

Set an iron post, 3 ft. long, 1" dia., 18" in the ground, to bedrock and build a mound of stone, 3 ft. base, 1 ft. high, around the post, for ¼ sec. cor. of sec. 13 only, with brass cap marked

¼
S 13
1928

from which

A W.Fir, 40" dia., bears N.27½°W., 127 lks. mkd: ¼S S13 BT
No other tree available in Sec. 13

Obliterate old ¼ sec. cor. without taking a tie to it.
The (1923) ¼ corner, by Mensch & Wilkes (Vol. 26 Pg 11142), established for secs. 13 & 18, H Raymond fd that there was an error on the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012