

TOWNSHIP 30 RANGE 03E POINT IDENTIFIER # 100496

PRIMARY CORNER DESCRIPTION East Cor. Secs. 12 & 13 only; T30-2E

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Herbert N Raymond, U.S. Cadastral Engineer, under Special Instructions dated Dec. 27, 1920 & Sept. 9, 1927 - (DCSO records Vol. 26 Page(s) 11049-50)

Set an iron post, 3 ft. long, 2" dia., 27" in the ground for cor. of secs. 12 & 13 only, with brass cap mkd:

T30S		T30S
S 12		R3E
S 13		S 18
R 2 E		
1928		

No BTs available, build a mound of stone, 3 ft. base; 1½ ft. high, 5 lks. W. of cor.

A cross (X) cut on a country rock, in place, 30" E & W 20" N & S and 15" high, bears N.10°W., 11 lks. mkd. B O below the cross

The (1923) corner, by Mensch & Wilkes (Vol. 26 Pg 11142), established for secs. 7, 12, 13, & 18, on line (S.0°13'W., 6.02 chs and West 62 lks.). We obliterate this corner.

H Raymond fd that there was an error in the 1923 survey by Mensch & Wilkes (see note pg 11026-7) - DCSO, JC 6/6/2012